



## MicroKlear 116AL

A micronized composite of polyethylene, carnauba wax and aluminum oxide for maximum scratch resistance with excellent clarity and gloss retention

### Features and Benefits

- HPDE/carnauba wax composite reinforced with 300 nm aluminum oxide nanoparticles (Mohs Hardness 9)
- Provides maximum scratch resistance with surface lubricity
- In coil coatings, provides maximum slip for forming and fabrication of finished coil
- Reduces coil coating surface haze post-bake and water quench
- Provides excellent slip, scratch resistance and food release properties in metal packaging coatings

### Composition

Polyethylene/carnauba wax/aluminum oxide

### Recommended Addition Levels

1.0-3.0% (on total formula weight)

### Systems and Applications

Water based, solvent based and energy curable coatings and inks. Industrial coatings (including plastic, metal and leather); wood coatings; printing inks and OPV's (including flexo and gravure); interior and exterior can and container coatings; coil coatings; seed coatings.

### Typical Properties\*

MicroKlear 116AL

<b>Melting Point °C</b>	107 - 113
<b>Density @ 25 °C (g/cc)</b>	1.01
<b>NPIRI Grind</b>	1.5 - 2.5
<b>Maximum Particle Size (µm)</b>	15.56
<b>Mean Particle Size (µm)</b>	3.5 - 5.5

Mar-23