



## Microspersion® 1226XF-50

A nonionic water based dispersion of a highly engineered HDPE/ceramic/nanoceramic composite for abrasion resistance and lubricity

### Features and Benefits

- Convenient, ready-to-use, pourable nonionic wax dispersion
- HDPE composite reinforced with hard, inert ceramic microspheres and nanoceramic platelets
- Improved Taber abrasion resistance when compared to PE/PTFE additives
- Provides slip and lubricity
- Ideal for can and container coatings; 21CFR 175.300 approved
- Effective replacement for PTFE additives

### Dry Wax ID

PolyGlide 1226XF

### Recommended Addition Levels

2.0-5.0% (on total formula weight)

### Systems and Applications

Water based coatings and inks. Industrial coatings (including plastic and metal); stains, sealers and varnishes; wood coatings; printing inks and OPV's (including flexo and gravure); can, container, and coil coatings; rubber additives.

### Typical Properties\*

**Microspersion 1226XF-50**

<b>Wax Solids</b>	50%
<b>Viscosity @ 25 °C (cP)</b>	2,000 - 9,000
<b>pH</b>	6.0 - 8.0
<b>Density @ 25 °C (g/cc)</b>	0.99
<b>Wax Mean Particle Size (µm)</b>	3.5 - 5.5
<b>NPIRI Grind</b>	1.0 - 2.0

Mar-23